

Small Bi-Metal Thermometers

1" Dial Size Pocket Thermometer

Model No.	Range
1R05E	-50 to 100°C
1R05F	-10 to 110°C
1R05G	0 to 150°C
1R05H	0 to 250°C

- 125mm (5" Stem length)
- 3.6mm stem diameter
- complete with pocket case & clip



2" Dial Size Thermometer



- All stainless steel construction
- Accurate to 1% of scale range
- Dual scale °F and °C
- 3.6mm stem diameter

Model No.	Range (all dual)	Stem Length
2R08A	-40 to 72°C	202mm (8") Plain stem with recalibration feature
2R08B	-4 to 52°C	
2R08J	-18 to 83°C	
2R08C	-18 to 105°C	
2R08K	10 to 106°C	
2R08D	10 to 290°C	
2T02A	-40 to 72°C	63mm (2 1/2") stem 1/4" NPT fixed thread
2T02C	-18 to 105°C	
2T04A	-40 to 72°C	100mm (4") stem 1/4" NPT fixed thread
2T04B	-4 to 52°C	
2T04C	-18 to 105°C	

63mm Spring or Magnetic Mount

63mm Steel/Aluminium Case.
Dual Scale °F and °C.



Model No.	Type	Range
BR33/401/0	Spring	0 to 120°C
BR33/402/0	Spring	0 to 200°C
BR33/409/0	Magnet	0 to 120°C
BR33/410/0	Magnet	0 to 200°C

Other ranges available.

Small General Purpose

Low-priced quality bimetal.
63mm Steel Case.
Brass thermowell included.
1/2" BSPP connection
(on thermowell).



Range 0/120°C stocked.
Other ranges available.
Recalibration feature.

Sales of ALL products are subject to our General Conditions of Quotation & Supply.
Technical specifications are subject to change without prior notice.